

It's Strong ... It's Sturdy

It's a

SKY CLIMBER

CX 500



Operate in your work environment

- Sandblasting
- Commercial Restoration
- Painting
- Masonry
- Window Cleaning
- General Building Maintenance
- Off Shore oil rigs
- Boiler and digester Maintenance
- Ship Maintenance
- Caulking

Whether you need to reach, new heights or fit into tight places, or both, turn to Sky Climber.

The CX 500 hoist from Sky Climber is the latest addition to the innovative family of specialized suspended platforms hoists.

This specially designed hoist lifts a heavy load (500kg) and have a self-weight of less than 41 kg.

Count on Sky Climber ... backed by more than 40 years industry experience, known for many innovative, industry first achievements. CX 500 leading a safe, fast and strong way into the future.

Lifts 500 kg
Operating Speed: 8,5 m/minute
Features the Sky Lock III
Hoist self-weight is 41 kg

The CX 500 is

- Engineered for safety, speed and power
- Designed for heavy duty field use

Put the CX 500 to use on

- a bosun seat
- a one man work cage
- a work platform, from 2 to 16 m

See how the CX 500's sleek tested design allows it to fit through a manhole as small as 47 cm, to lift your heaviest loads to 500 kg. This 41 kg of innovation will save you time and money.

It lifts more and weighs less !



MEMBER
SIA
ASSOCIATION

N.V. SKY CLIMBER EUROPE S.A. – BOOMSESTEENWEG 14 - B – 2630 AARTSELAAR
E-mail: info@skyclimber.be Web site <http://www.skyclimber.com>
Tel : +32 (0)3 887 81 20 Fax : +32 (0)3 887 09 94



Hoist with Sky Lock Dimensions :

Height : 64 cm
 Width : 40 cm
 Length : 45 cm

Hoist Self-Weight : 41 kg (Air 33 kg)
 Rated Load Capacity: 500 kg
 Operating Speed : 8,5 m/min.

Hoist Safety Features :

- Sky Lock III overspeed secondary brake.
- No Power Emergency controlled descent with manual brake release.
- Meets CE Requirements.

Unique Patented Traction Sheave :

Ensures equal pressure on steel wire rope around the circumference of the sheave and gives unlimited working height at constant speed and capacity.

Sky Lock III Independent Safety Device :

One of the important safety features of the Sky Climber hoist is the Sky Lock, a dynamic safety device which senses rope speed as it passes through the mechanism. If the hoist exceeds the factory pre-set speed of 25m/min. the Sky Lock will automatically trip and lock onto the secondary safety wire rope and support the load.

By activating the manual trip mechanism, it is possible for any sub-assembly of the hoist to be removed safely, while the platform is suspended from the Sky Lock.

Power/ Electrical Requirements :

Motor Options	Power	Line Current
220-240V/50Hz/Single phase	0,88 kW	5,25 A
380-415V/50Hz/Three phase Other motor option upon request	0,88 kW	3,1 A
Pneumatic	0,85 kW	1,7m ³ /min.@5 bar

To meet the unified CE regulations, SKY LOCK should be mounted on a secondary steel wire rope.

- Options :
- Hoist mounted
 - End Stirrup mounted
 - Walk through stirrup mounted

Hoist Controls Options :


- Pendant or Central
- 24 V Control Circuit

Gearbox :

Maintenance free, high efficiency , double planetary gearbox with 95% efficiency.

Wire Rope Requirements :

Rope diameter 8 mm
 Theoretical breaking load 49,2 kN
 Actual Breaking Load 44,6 kN



Additional Sky Lock Applications

Although designed to be used with Sky Climber hoists, the Sky Lock III has found other uses as an independent safety device. On oil drillings rigs it is used with derrick climbers as a descent control device and on special purpose elevators as a brake. Requiring no external power source, the Sky Lock III is available for additional special applications.

**Call Sky Climber First
 + 32 (0) 3 887 81 20
 or your nearest
 Sky Climber distributor**

Your local representative :



SKY CLIMBER FIRST

SAFETY • SERVICE • SOLUTIONS